

MODEL	NPR 400 AMT	NPR 400 CREW AMT	NQR 500	NQR 500 AMT	NQR 500 SWB
<b>AXLE LAYOUT</b>	4X2	4X2	4X2	4X2	4X2
<b>CONTROL</b>	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD
<b>MASS</b>					
Permissible Body + Payload (kg)	4 840	4 600	5 700	5 680	5 720
Tare Total (T) (kg)	2 660	2 900	2 800	2 820	2 780
Front Tare (kg)	1 740	1 900	1 810	1 830	1 800
Rear Tare (kg)	920	1 000	990	990	980
GVM (kg)	7 500	7 500	8 500	8 500	8 500
V (kg)	7 500	7 500	8 500	8 500	8 500
GCM (kg)	11 000	11 000	12 000	12 000	12 000
D/T (kg)	11 000	11 000	12 000	12 000	12 000
Front Axle – GA/GAU (kg)	3 100	3 100	3 100	3 100	3 100
Front Axle – A/AU (kg)	2 900	2 900	3 100	3 100	3 100
Rear Axle – GA/GAU (kg)	6 600	6 600	6 600	6 600	6 600
Rear Axle – A/AU (kg)	5 600	5 600	6 600	6 600	6 600
Litres of Fuel Tank 1 Included in Tare	15	15	15	15	15
Litres of Fuel Tank 2 Included in Tare	0	0	0	0	0
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes	Yes	Yes	Yes	Yes
<b>PERFORMANCE</b>					
Gradeability @ V (%)	32	32	32	32	32
Gradeability @ D/T (%)	22	22	23	23	23
Max. Geared Road Speed (km/h)	116 (111)	116 (111)	107	107	107
<b>MAJOR DIMENSIONS</b>					
OL – Overall Length (mm)	6 635	6 635	7 355	7 355	5 985
OW – Overall Width (mm)	1 995	1 995	1 995	1 995	1 995
WB – Wheelbase (mm)	3 815	3 815	4 175	4 175	3 365
CA – Cab to Bogie / Rear Axle (mm)	3 242	2 241	3 602	3 602	2 792
CE – Cab to End of Chassis (mm)	4 952	3 961	5 672	5 672	4 302
OH – Overall Height (mm)	2 270 (2 253)	2 270 (2 253)	2 275	2 275	2 275
FOH – Front Overhang (mm)	1 110	1 110	1 110	1 110	1 110
ROH – Rear Overhang (mm)	1 710	1 710	2 070	2 070	1 510
EH – Chassis Rear End Height (mm)	845 (828)	845 (828)	855	855	845
HH – Ground Clearance (mm)	195 (178)	195 (178)	205	205	195
Rear Chassis Width (mm)	850	850	850	850	850
Turning Radius – Curb to Curb (mm)	7 150	7 150	7 800	7 800	6 400
Turning Radius – Wall to Wall (mm)	7 900	7 900	8 500	8 500	7 150
<b>ENGINE</b>					
Make	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu
Model	4HK1-TCN	4HK1-TCN	4HK1-TCN	4HK1-TCN	4HK1-TCN
Capacity (cm <sup>3</sup> )	5 193	5 193	5 193	5 193	5 193
Layout	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4
Type	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	110 @ 2 600	110 @ 2 600	110 @ 2 600	110 @ 2 600	110 @ 2 600
Torque @ r/min (Nm)	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600
Emissions – Standard	Euro 3	Euro 3	Euro 2	Euro 3	Euro 2
<b>CLUTCH</b>					
Make	N/A	N/A	Exedy	N/A	Exedy
Model	N/A	N/A	325	N/A	325
Type	N/A	N/A	Single	N/A	Single
Diameter (mm)	N/A	N/A	325	N/A	325
Operation	Automated Hydraulic-Controlled Wet Clutch	Automated Hydraulic-Controlled Wet Clutch	Hydraulic-Assisted	Automated Hydraulic-Controlled Wet Clutch	Hydraulic-Assisted
<b>TRANSMISSION</b>					
Make	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu
Model	MY65 (AMT)	MY65 (AMT)	MY65	MY65 (AMT)	MY65
Type	6-Speed Synchronesh	6-Speed Synchronesh	6-Speed Synchronesh	6-Speed Synchronesh	6-Speed Synchronesh
Shift	Automated Manual (AMT)	Automated Manual (AMT)	Manual Gearshift	Automated Manual (AMT)	Manual Gearshift
No. of Gears Forward	6	6	6	6	6
First Gear Ratio : 1	5.979	5.979	5.979	5.979	5.979
Top Gear Ratio : 1	0.759	0.759	0.759	0.759	0.759
Transfer Case	No	No	No	No	No
PTO (Power Take-Off)	Optional	Optional	Optional	Optional	Optional
<b>DRIVE AXLE</b>					
Make	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu
Model Front Axle	F031	F031	F031	F031	F031
Model Rear Axle	R066	R066	R066	R066	R066
Reduction Type	Single	Single	Single	Single	Single
Final Ratio : 1	4.556	4.556	5.125	5.125	5.125
<b>SUSPENSION</b>					
Front	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs
Rear	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs
Shock Absorbers	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear
Stabilisers	Yes	Yes	Yes	Yes	Yes
<b>STEERING</b>					
Operation	Power	Power	Power	Power	Power
<b>BRAKES</b>					
System Type	Hydraulic Brake Boost	Hydraulic Brake Boost	Hydraulic Brake Boost	Hydraulic Brake Boost	Hydraulic Brake Boost
Front	Drums	Drums	Discs	Discs	Discs
Rear	Drums	Drums	Drums	Drums	Drums
Anti-Lock Braking System (ABS)	Standard	Standard	Standard	Standard	Standard
Park / Emergency System	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft
Exhaust Brake	Standard	Standard	Standard	Standard	Standard
<b>ELECTRICAL &amp; FUEL</b>					
Fuel Tank 1 Capacity (Litres)	100	100	100	100	100
Fuel Tank 2 Capacity (Litres)	0	0	0	0	0
<b>TYRES</b>					
Size & Ply Rating – Front	7.50 R16 - 12PR (215 / 75 R17.5)	7.50 R16 - 12PR (215 / 75 R17.5)	225 / 70 R19.5	225 / 70 R19.5	225 / 70 R19.5
Size & Ply Rating – Rear	7.50 R16 - 12PR (215 / 75 R17.5)	7.50 R16 - 12PR (215 / 75 R17.5)	225 / 70 R19.5	225 / 70 R19.5	225 / 70 R19.5
<b>CAB &amp; EXTRAS</b>					
Type	Day	Crew	Day	Day	Day
Roof	Low	Low	Low	Low	Low
No. of Bunks	0	0	0	0	0
No. of Seats (Lap, Rear & Centre)	3	7	3	3	3
Air-Conditioning	Optional	Optional	Optional	Optional	Optional
Radio / CD / Speakers	Standard	Standard	Optional	Standard	Optional
Central Locking	Standard	Standard	Standard	Standard	Standard
Electric Windows	Standard	Standard	Standard	Standard	Standard
Tilt Cab	Yes	No	Yes	Yes	Yes

The information herein is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. E&OE. Model/s shown may differ. Date of print October 2019.

# N-SERIES

## Specification Sheet

# RANGE



**THERE'S  
WORK  
TO DO**

**ISUZU**

*With you, for the long run*



MODEL	NLR 150	NMR 250	NMR 250 SWB AMT	NMR 250 AMT	NMR 250 CREW AMT	NPR 275 AMT	NPR 300	NPR 300 AMT	NPS 300	NPS 300 SWA	NPS 300 SWA CREW CAB	NPS 300 CREW CAB	NPR 400	NPR 400 SWB
AXLE LAYOUT	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X4	4X4	4X4	4X4	4X2	4X2
CONTROL	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD	FORWARD
<b>MASS</b>														
Permissible Body + Payload (kg)	2 260	3 130	3 180	3 100	2 920	3 420	3 680	3 680	3 210	3 200	3 140	3 150	4 880	4 920
Tare Total (T) (kg)	1 940	2 070	2 020	2 100	2 280	2 380	2 520	2 520	2 790	2 800	3 060	3 050	2 620	2 580
Front Tare (kg)	1 390	1 400	1 420	1 400	1 520	1 560	1 670	1 700	1 830	1 880	1 830	1 830	1 710	1 700
Rear Tare (kg)	550	670	600	670	760	820	850	870	960	920	960	960	900	880
GVM (kg)	4 200	5 200	5 200	5 200	5 200	5 800	6 200	6 200	6 000	6 000	6 200	6 200	7 500	7 500
V (kg)	4 200	5 200	5 200	5 200	5 200	5 800	6 200	6 200	6 000	6 000	6 200	6 200	7 500	7 500
GCM (kg)	7 050	8 700	8 700	8 700	8 700	9 700	9 700	9 700	9 500	9 500	9 500	9 500	11 000	11 000
D/T (kg)	7 050	8 700	8 700	8 700	8 700	9 700	9 700	9 700	9 500	9 500	9 500	9 500	11 000	11 000
Front Axle – GA/GAU (kg)	2 900	2 900	2 900	2 900	2 900	3 100	3 100	3 100	2 800	2 800	2 800	2 800	3 100	3 100
Front Axle – A/AU (kg)	1 950	2 300	2 300	2 300	2 300	2 900	2 900	2 900	2 800	2 800	2 800	2 800	2 900	2 900
Rear Axle – GA/GAU (kg)	5 000	5 000	5 000	5 000	5 000	6 000	6 000	6 000	6 600	6 600	6 600	6 600	6 600	6 600
Rear Axle – A/AU (kg)	3 700	4 480	4 480	4 480	4 480	5 600	5 600	5 600	4 240	4 240	4 240	5 600	5 600	
Litres of Fuel Tank 1 Included in Tare	15	15	15	15	15	15	15	15	15	15	15	15	15	15
Litres of Fuel Tank 2 Included in Tare	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>PERFORMANCE</b>														
Gradeability @ V (%)	52	43	43	43	43	37	37	37	43/80	43/80	43/80	43/80	32	32
Gradeability @ D/T (%)	31	26	26	26	26	22	24	24	27/50	27/50	27/50	27/50	22	22
Max. Geared Road Speed (km/h)	133	122	122	122 (118)	118 (113)	103	121	121 (116)	104	104	104	104	116	116
<b>MAJOR DIMENSIONS</b>														
OL – Overall Length (mm)	4 730	5 915	4 730	5 915	6 020	5 985	5 985	5 985	5 985	5 985	5 985	5 985	6 635	5 985
OW – Overall Width (mm)	1 770	1 770	1 770	1 770	1 770	1 995	1 995	1 995	1 995	1 995	1 995	1 995	1 995	1 995
WB – Wheelbase (mm)	2 475	3 345	2 475	3 345	3 345	3 395	3 365	3 365	3 395	3 395	3 395	3 395	3 815	3 365
CA – Cab to Bogie / Rear Axle (mm)	2 022	2 892	2 022	2 892	1 771	2 792	2 792	2 792	2 882	2 882	1 821	1 821	3 242	2 792
CE – Cab to End of Chassis (mm)	3 167	4 457	3 167	4 457	3 346	3 346	4 302	4 302	4 302	4 302	3 301	3 301	4 952	4 302
OH – Overall Height (mm)	2 150	2 160	2 160	2 160	2 220 (2 188)	2 253	2 265	2 270 (2 253)	2 265	2 265	2 265	2 265	2 255	2 265
FOH – Front Overhang (mm)	1 110	1 105	1 105	1 105	1 105	1 110	1 110	1 110	1 110	1 110	1 110	1 110	1 110	1 110
ROH – Rear Overhang (mm)	1 145	1 455	1 145	1 585	1 455	1 585	1 510	1 510	1 510	1 510	1 510	1 510	1 710	1 510
EH – Chassis Rear End Height (mm)	760	810	810	810	810 (758)	828	845	845 (828)	975	1 000	1 000	975	845	845
HH – Ground Clearance (mm)	200	210	210	210	210 (178)	178	195	195 (178)	210	235	235	210	195	195
Rear Chassis Width (mm)	700	700	700	700	700	750	850	850	850	850	850	850	850	850
Turning Radius – Curb to Curb (mm)	5 250	7 250	5 250	7 250	7 250	6 400	6 400	6 400	6 450	6 450	6 450	6 450	7 150	6 400
Turning Radius – Wall to Wall (mm)	5 800	7 950	5 800	7 950	7 950	7 150	7 150	7 150	7 200	7 200	7 200	7 200	7 900	7 150
<b>ENGINE</b>														
Make	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu
Model	4JJ1-TC	4JJ1-TC	4JJ1-TC	4JJ1-TC	4JJ1-TC	4JJ1-TC	4HK1-TCN	4HK1-TCN	4HK1-TCN	4HK1-TCN	4HK1-TCN	4HK1-TCN	4HK1-TCN	4HK1-TCN
Capacity (cm <sup>3</sup> )	2 999	2 999	2 999	2 999	2 999	2 999	5 193	5 193	5 193	5 193	5 193	5 193	5 193	5 193
Layout	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4	Diesel Inline-4
Type	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	96 @ 2 800	96 @ 2 800	96 @ 2 800	96 @ 2 800	96 @ 2 800	96 @ 2 800	110 @ 2 600	110 @ 2 600	110 @ 2 600	110 @ 2 600	110 @ 2 600	110 @ 2 600	110 @ 2 600	110 @ 2 600
Torque @ r/min (Nm)	330 @ 1 600 – 2 600	330 @ 1 600 – 2 600	330 @ 1 600 – 2 600	330 @ 1 600 – 2 600	330 @ 1 600 – 2 600	330 @ 1 600 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600	404 @ 1 500 – 2 600
Emissions – Standard	Euro 2	Euro 2	Euro 3	Euro 3	Euro 3	Euro 3	Euro 2	Euro 3	Euro 2	Euro 2	Euro 2	Euro 2	Euro 2	Euro 2
<b>CLUTCH</b>														
Make	Exedy	Exedy	N/A	N/A	N/A	N/A	Exedy	N/A	Exedy	Exedy	Exedy	Exedy	Exedy	Exedy
Model	300	300	N/A	N/A	N/A	N/A	325	N/A	325	325	325	325	325	325
Type	Single	Single	N/A	N/A	N/A	N/A	Single	N/A	Single	Single	Single	Single	Single	Single
Diameter (mm)	300	300	N/A	N/A	N/A	N/A	325	N/A	325	325	325	325	325	325
Operation	Hydraulic-Assisted	Hydraulic-Assisted	Automated Hydraulic-Controlled Wet Clutch	Hydraulic-Assisted	Automated Hydraulic-Controlled Wet Clutch	Automated Hydraulic-Controlled Wet Clutch	Hydraulic-Assisted	Automated Hydraulic-Controlled Wet Clutch	Hydraulic-Assisted	Hydraulic-Assisted	Hydraulic-Assisted	Hydraulic-Assisted	Hydraulic-Assisted	Hydraulic-Assisted
<b>TRANSMISSION</b>														
Make	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu
Model	MYYST	MYYST	MYYS6S (AMT)	MYYS6S (AMT)	MYYS6S (AMT)	MYYS6S (AMT)	MYYS6S	MYYS6S (AMT)	MYYST	MYYST	MYYST	MYYS6S	MYYS6S	MYYS6S
Type	5-Speed Synchronesh	5-Speed Synchronesh	6-Speed Synchronesh	6-Speed Synchronesh	6-Speed Synchronesh	6-Speed Synchronesh	6-Speed Synchronesh	6-Speed Synchronesh	5-Speed Synchronesh	5-Speed Synchronesh	5-Speed Synchronesh	5-Speed Synchronesh	6-Speed Synchronesh	6-Speed Synchronesh
Shift	Manual Gearshift	Manual Gearshift	Automated Manual (AMT)	Automated Manual (AMT)	Automated Manual (AMT)	Automated Manual (AMT)	Manual Gearshift	Automated Manual (AMT)	Manual Gearshift	Manual Gearshift	Manual Gearshift	Manual Gearshift	Manual Gearshift	Manual Gearshift
No. of Gears Forward	5	5	6	6	6	6	6	6	5	5	5	5	6	6
First Gear Ratio : 1	5.315	5.315	5.979	5.979	5.979	5.979	5.979	5.979	5.315 H / 9.790 L	5.315 H / 9.790 L	5.315 H / 9.790 L	5.315 H / 9.790 L	5.979	5.979
Top Gear Ratio : 1	0.721	0.721	0.759	0.759	0.759	0.759	0.759	0.759	0.721 H / 1.328 L	0.721 H / 1.328 L	0.721 H / 1.328 L	0.721 H / 1.328 L	0.759	0.759
Transfer Case	No	No	No	No	No	No	No	No	Yes	Yes	Yes	Yes	No	No
PTO (Power Take-Off)	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
<b>DRIVE AXLE</b>														
Make	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu	Isuzu
Model Front Axle	F029	F029	F029	F029	F029	F031	F031	F031	FD028	FD028	FD028	FD028	F031	F031
Model Rear Axle	R045	R050	R050	R050	R050	R066	R066	R066	R066	R066	R066	R066	R066	R066
Reduction Type	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single
Final Ratio : 1	4.100	5.125	5.125	5.125	5.125	5.375	5.857	4.300	5.125	5.125	5.125	5.125	4.556	4.556
<b>SUSPENSION</b>														
Front	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs
Rear	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs	Semi-Elliptic Springs
Shock Absorbers	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear
Stabilisers	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>STEERING</b>														
Operation	Power	Power	Power	Power	Power	Power	Power	Power	Power	Power	Power	Power	Power	Power
<b>BRAKES</b>														
System Type	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Vacuum Hydraulic	Hydraulic Brake Boost	Hydraulic Brake Boost
Front	Discs	Discs	Discs	Discs	Discs	Discs	Discs	Discs	Drums	Drums	Drums	Drums	Drums	Drums
Rear	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums
Anti-Lock Braking System (ABS)	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Park / Emergency System	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft
Exhaust Brake	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
<b>ELECTRICAL &amp; FUEL</b>														
Fuel Tank 1 Capacity (Litres)	75	100	100	100	100	100	100	100	100	100	100	100	100	100
Fuel Tank 2 Capacity (Litres)	0	0	0	0	0	0	0	0	0	0	0	0	0	0
<b>TYRES</b>														
Size & Ply Rating – Front	195 / 75 R16C	700 R16 - 10PR	700 R16 - 10PR	700 R16 - 10PR (205 / 75 R16C)	750 R16 - 12PR (215 / 75 R17.5)	215 / 75 R17.5	750 R16 - 12PR	750 R16 - 12PR (2						